Login Choice.aspx:

```
<%@ Page Language="VB" AutoEventWireup="true" CodeFile="LoginChoice.aspx.vb"
Inherits="LoginChoice" %>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Login Choice</title>
    <link rel="stylesheet" href="style.css" />
</head>
<body>
<form id="form1" runat="server">

<div class="container">
    <h2>Login As</h2>

    <asp:Button ID="btnEmployee" runat="server" Text="Employee" CssClass="btn"
OnClick="btnEmployee_Click" />
    <br /><br />

    <asp:Button ID="btnCustomer" runat="server" Text="Customer" CssClass="btn"
OnClick="btnCustomer_Click" />
</div>

</form>
</body>
</html>
```

Login Choice.aspx.vb:

```
Partial Class LoginChoice
    Inherits System.Web.UI.Page

    Protected Sub btnEmployee_Click(sender As Object, e As EventArgs)
        Response.Redirect("EmployeeLogin.aspx")
    End Sub

    Protected Sub btnCustomer_Click(sender As Object, e As EventArgs)
    Response.Redirect("index.aspx") ' MAIN CUSTOMER WEBSITE End
    Sub

End Class
```

Employee Login:

.aspx

```
<%@ Page Language="VB" AutoEventWireup="true" CodeFile="EmployeeLogin.aspx.vb"
Inherits="EmployeeLogin" %>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Employee Login</title>
    <link rel="stylesheet" href="style.css" />
</head>

<body>
<form id="form1" runat="server">

<div class="auth-box">
    <h2>Employee Login</h2>

    <asp:TextBox ID="txtEmail" runat="server" Placeholder="Email"></asp:TextBox>
<asp:TextBox ID="txtPassword" runat="server" TextMode="Password"
Placeholder="Password"></asp:TextBox>

    <asp:Button ID="btnLogin" runat="server" Text="Login" CssClass="btn"
OnClick="btnLogin_Click" />
    <asp:Label ID="lblMsg" runat="server" ForeColor="Red"></asp:Label>

</div>

</form>
</body>
</html>
```

Employee_login.aspx.vb:

```
Partial Class EmployeeLogin
    Inherits System.Web.UI.Page

    Protected Sub btnLogin_Click(sender As Object, e As EventArgs)

        ' Hardcoded employee login (for assignment)
        If txtEmail.Text = "admin" And txtPassword.Text = "1234" Then

            ' Save session (to protect dashboard)
            Session("Employee") = txtEmail.Text
```

```
          ' Redirect to Employee Dashboard
          Response.Redirect("employee_dashboard.aspx")

      Else
          lblMsg.Text = "Invalid Email or Password"
      End If

    End Sub

End Class
```

Employee_Dashboard
.aspx:

```
<%@ Page Language="VB" AutoEventWireup="true" CodeFile="employee_dashboard.aspx.vb"
Inherits="employee_dashboard" %>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Employee Dashboard</title>
    <link rel="stylesheet" href="style.css" />
</head>
<body>
<form id="form1" runat="server">

<header>
    <h1>Employee Dashboard</h1>
</header>

<!-- Navigation Menu -->
<nav>
    <ul>
      <li>
        <asp:HyperLink ID="hlUpdateCatalog" runat="server"
NavigateUrl="update_catalog.aspx" Text="Update Product Catalog" />
      </li>
      <li>
```

```
          <asp:HyperLink ID="btnLogout" runat="server" NavigateUrl="LoginChoice.aspx"
Text="Logout" />
      </li>
    </ul>
</nav>

<div class="container">
   <h2>Welcome, Employee!</h2>
   <p>Select an option from the menu above to proceed.</p>
</div>


</form>
</body>
</html>
```

Employee_Dashboard.aspx.vb:

```
Partial Class employee_dashboard
    Inherits System.Web.UI.Page

    Protected Sub Page_Load(sender As Object, e As EventArgs) Handles Me.Load
        If Session("Employee") Is Nothing Then
            Response.Redirect("EmployeeLogin.aspx")
        End If
    End Sub

    Protected Sub btnLogout_Click(sender As Object, e As EventArgs)
        Session.Clear()
        Response.Redirect("LoginChoice.aspx")
    End Sub

End Class
```

Update_Catalog.aspx:

```
<%@ Page Language="VB" AutoEventWireup="true"
CodeFile="update_catalog.aspx.vb" Inherits="update_catalog" %>

<!DOCTYPE html>
<html>
<head runat="server">
```

```html
    <title>Update Catalog</title>
    <link href="style.css" rel="stylesheet" />
</head>
<body>
<form id="form1" runat="server">

    <h2>Product Catalog Update</h2>


    Product ID:
    <asp:TextBox ID="txtProductIDSearch" runat="server"></asp:TextBox>
    <asp:Button ID="btnSearch" runat="server" Text="Search" /><br /><br />


    Product ID:
    <asp:Label ID="lblProductID" runat="server" Text=""></asp:Label><br /><br />

    Product Line ID:
    <asp:TextBox ID="txtLineID" runat="server"></asp:TextBox><br /><br />

    Product Description:
    <asp:TextBox ID="txtDesc" runat="server"></asp:TextBox><br /><br />

    Product Finish:
    <asp:TextBox ID="txtFinish" runat="server"></asp:TextBox><br /><br />

    Standard Price:
    <asp:TextBox ID="txtPrice" runat="server"></asp:TextBox><br /><br />

    <asp:Button ID="btnConfirm" runat="server" Text="Confirm Changes"
Enabled="False" /><br /><br />

    <asp:Label ID="lblMessage" runat="server" ForeColor="Red"></asp:Label>

</form>
</body>
</html>
```

UpdateCatalog.aspx.vb:

```vb
Imports System.Configuration
Imports System.Data.SqlClient

Partial Class update_catalog
    Inherits System.Web.UI.Page

    Dim connStr As String =
ConfigurationManager.ConnectionStrings("PVFCConnectionString").ConnectionString


    Protected Sub btnSearch_Click(sender As Object, e As EventArgs) Handles btnSearch.Click

        If txtProductIDSearch.Text = "" Then
            lblMessage.Text = "Please enter Product ID"
            Exit Sub
        End If

        Dim conn As New SqlConnection(connStr)

        Dim query As String = "SELECT * FROM PRODUCT_t WHERE Product_Id = " &
txtProductIDSearch.Text
        Dim cmd As New SqlCommand(query, conn)

        Try
            conn.Open()
            Dim reader As SqlDataReader = cmd.ExecuteReader()

            If reader.Read() Then
                lblProductID.Text = reader("Product_Id").ToString()
                txtLineID.Text = reader("Product_Line_Id").ToString()
                txtDesc.Text = reader("Product_Description").ToString()
                txtFinish.Text = reader("Product_Finish").ToString()
                txtPrice.Text = reader("Standard_Price").ToString()

                lblMessage.Text = "Product Found!"
                btnConfirm.Enabled = True
            Else
                lblMessage.Text = "Product not found!"
                lblProductID.Text = ""
                txtLineID.Text = ""
```

```vbnet
            txtDesc.Text = ""
            txtFinish.Text = ""
            txtPrice.Text = ""
            btnConfirm.Enabled = False
        End If

        conn.Close()

    Catch ex As Exception
        lblMessage.Text = "Error: " & ex.Message
    End Try

End Sub

' UPDATE BUTTON
Protected Sub btnConfirm_Click(sender As Object, e As EventArgs) Handles
btnConfirm.Click

    If lblProductID.Text = "" Then
        lblMessage.Text = "No product selected to update"
        Exit Sub
    End If

    Dim conn As New SqlConnection(connStr)
    Dim query As String = "UPDATE PRODUCT_t SET " &
                "Product_Line_Id = " & txtLineID.Text & ", " &
                "Product_Description = '" & txtDesc.Text & "', " &
                "Product_Finish = '" & txtFinish.Text & "', " &
                "Standard_Price = " & txtPrice.Text & " " &
                "WHERE Product_Id = " & lblProductID.Text

    Dim cmd As New SqlCommand(query, conn)

    Try
        conn.Open()
        cmd.ExecuteNonQuery()
        lblMessage.Text = "Changes saved successfully!"
        btnConfirm.Enabled = False
        conn.Close()
    Catch ex As Exception
        lblMessage.Text = "Error: " & ex.Message
```

End Try

              End Sub

        End Class

Home Page:

.aspx

```
<%@ Page Language="VB" AutoEventWireup="true" CodeFile="index.aspx.vb"
Inherits="_index" %>
<!DOCTYPE html>
<html>
<head runat="server">
    <title>Pine Valley Furniture</title>
    <link rel="stylesheet" href="style.css" />
</head>
<body>
    <form id="form1" runat="server">
        <header>
            <h1>Pine Valley Furniture</h1>
        </header>

        <nav>
            <ul>
                <li><a href="register.aspx">Customer Registration</a></li>
                <li><a href="search.aspx">Search Products</a></li>
                <li><a href="Cart.aspx">Cart</a></li>
                <li><a href="Help.aspx">Help</a></li>

            </ul>
        </nav>

        <div class="container">
            <h2>Welcome to Pine Valley Furniture</h2>
            <asp:HyperLink ID="ShopNowLink" runat="server" NavigateUrl="search.aspx">
            <asp:Button ID="btnShopNow" runat="server" Text="Shop Now" CssClass="btn" />
            </asp:HyperLink>
        </div>
```

```
        <footer>
            Contact us: 0309-5878126 | Email: hhm@gmail.com
        </footer>
    </form>
</body>
</html>
```

HomePage.aspx.vb

```
Partial Class _index
    Inherits System.Web.UI.Page

    Protected Sub Page_Load(sender As Object, e As EventArgs) Handles Me.Load
        ' Optional: Any code to run on page load
    End Sub
End Class
```

Customer Registration.aspx:

```
<%@ Page Language="VB" AutoEventWireup="false" CodeFile="Register.aspx.vb"
Inherits="Register" %>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Customer Registration</title>
    <link href="style.css" rel="stylesheet" />
</head>
<body>

<form id="form1" runat="server">

<header>
    <h1>Pine Valley Furniture - Customer Registration</h1>
</header>

<nav>
    <ul>
        <li><a href="Main.aspx">Home</a></li>
```

```
        <li><a href="Register.aspx">Register</a></li>
        <li><a href="Cart.aspx">Cart</a></li>
    </ul>
</nav>

<div class="container">

    <div class="auth-box">

        <h2>New Customer</h2>

        <asp:TextBox ID="txtCustomerId" runat="server"
            CssClass="input-field" placeholder="Customer ID" />
        <br /><br />

        <asp:TextBox ID="txtName" runat="server"
            CssClass="input-field" placeholder="Customer Name" />
        <br /><br />

        <asp:TextBox ID="txtAddress" runat="server"
            CssClass="input-field" placeholder="Address" />
        <br /><br />

        <asp:TextBox ID="txtCity" runat="server"
            CssClass="input-field" placeholder="City" />
        <br /><br />

        <asp:TextBox ID="txtState" runat="server"
            CssClass="input-field" placeholder="State (2 letters)" />
        <br /><br />

        <asp:TextBox ID="txtPostal" runat="server"
            CssClass="input-field" placeholder="Postal Code" />
        <br /><br />

        <asp:Button ID="btnSubmit" runat="server"
            Text="Register"
            CssClass="btn"
            OnClick="btnSubmit_Click" />
```

```
            <br /><br />

            <asp:Label ID="lblMessage" runat="server" />

        </div>

    </div>

    </form>
    </body>
    </html>
```

Register.aspx.vb

```vb
Imports System.Data.SqlClient
Imports System.Configuration

Partial Class Register
    Inherits System.Web.UI.Page

    Dim connStr As String =
ConfigurationManager.ConnectionStrings("PVFCConnectionString").ConnectionString

    Protected Sub btnSubmit_Click(sender As Object, e As EventArgs)

        Dim conn As New SqlConnection(connStr)

        Dim query As String = "INSERT INTO CUSTOMER_t " &
                    "(Customer_Id, Customer_Name, Customer_Address,
Customer_City, Customer_State, Postal_Code) VALUES (" &
                    txtCustomerId.Text & ", '" &
                    txtName.Text & "', '" &
                    txtAddress.Text & "', '" &
                    txtCity.Text & "', '" &
                    txtState.Text & "', '" &
                    txtPostal.Text & "')"

        Dim cmd As New SqlCommand(query, conn)

        Try
            conn.Open()
```

```vb
            cmd.ExecuteNonQuery()
            lblMessage.ForeColor = Drawing.Color.Green
            lblMessage.Text = "Customer Registered Successfully!"
            conn.Close()
        Catch ex As Exception
            lblMessage.ForeColor = Drawing.Color.Red
            lblMessage.Text = "Error: " & ex.Message
        End Try

    End Sub

End Class
```

Search Products.aspx:

```aspx
<%@ Page Language="VB" AutoEventWireup="false" CodeFile="search.aspx.vb"
Inherits="search" %>

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title>Search Products - Pine Valley Furniture</title>
    <link rel="stylesheet" href="style.css" />
</head>
<body>

<form id="form1" runat="server">

<header>
    <h1>Search Products</h1>
</header>

<nav>
    <ul>
        <li><a href="main.aspx">Home</a></li>
        <li><a href="Cart.aspx">Cart</a></li>
    </ul>
```

```aspx
</nav>

<div class="container">

    <div style="margin-bottom:20px;">

        <asp:Label Text="Search Product:" runat="server" />

        <asp:TextBox
            ID="txtSearch"
            runat="server"
            style="padding:8px; border-radius:6px; border:1px solid #ccc;">
        </asp:TextBox>

        <asp:Button
            ID="btnSearch"
            runat="server"
            Text="Search"
            CssClass="btn"
            OnClick="btnSearch_Click" />

        <asp:Button
            ID="btnShowAll"
            runat="server"
            Text="Show All"
            CssClass="btn"
            OnClick="btnShowAll_Click" />

    </div>

    <asp:Label ID="lblMessage" runat="server"></asp:Label>

    <br /><br />

    <div class="product-grid">

        <asp:Repeater ID="rptProducts" runat="server"
OnItemCommand="rptProducts_ItemCommand">
            <ItemTemplate>
```

```
<div class="product-card">

    <div class="image-box"></div>

    <h3><%# Eval("Product_Description") %></h3>

    <p>Finish: <%# Eval("Product_Finish") %></p>

    <p><strong>$ <%# Eval("Standard_Price") %></strong></p>

    <div style="margin-top:10px;">
        Quantity:
        <asp:TextBox
            ID="txtQty"
            runat="server"
            Width="50px"
            style="padding:5px; border-radius:6px; border:1px solid #ccc;">
        </asp:TextBox>
    </div>

    <asp:Button
        ID="btnAdd"
        runat="server"
        Text="Add To Cart"
        CssClass="btn"
        style="margin-top:10px; width:100%;"
        CommandName="AddToCart"
        CommandArgument='<%# Eval("Product_Id") %>' />

</div>

        </ItemTemplate>
      </asp:Repeater>

  </div>

</div>
```

```
</form>
</body>
</html>
```

SearchProducts.aspx.vb:

```vb
Imports System.Data.SqlClient
Imports System.Configuration

Partial Class search
    Inherits System.Web.UI.Page

    Dim connStr As String =
ConfigurationManager.ConnectionStrings("PVFCConnectionString").ConnectionString

    Protected Sub btnSearch_Click(sender As Object, e As EventArgs)

        Dim con As New SqlConnection(connStr)

        Dim query As String = "SELECT Product_Id, Product_Description, Product_Finish,
Standard_Price " &
                        "FROM PRODUCT_t WHERE Product_Description LIKE '%" &
txtSearch.Text & "%'"

        Dim cmd As New SqlCommand(query, con)

        con.Open()
        Dim dr As SqlDataReader = cmd.ExecuteReader()

        rptProducts.DataSource = dr
        rptProducts.DataBind()

        con.Close()

    End Sub

    Protected Sub btnShowAll_Click(sender As Object, e As EventArgs)

        Dim con As New SqlConnection(connStr)

        Dim query As String = "SELECT Product_Id, Product_Description, Product_Finish,
```

```vbnet
Standard_Price FROM PRODUCT_t"

        Dim cmd As New SqlCommand(query, con)

        con.Open()
        Dim dr As SqlDataReader = cmd.ExecuteReader()

        rptProducts.DataSource = dr
        rptProducts.DataBind()

        con.Close()

    End Sub

    Protected Sub rptProducts_ItemCommand(source As Object, e As
RepeaterCommandEventArgs)

        If e.CommandName = "AddToCart" Then

            Dim productId As Integer = Convert.ToInt32(e.CommandArgument)
            Dim txtQty As TextBox = CType(e.Item.FindControl("txtQty"), TextBox)

            If txtQty.Text = "" Then
                lblMessage.Text = "Enter quantity."
                Exit Sub
            End If

            Dim quantity As Integer = Convert.ToInt32(txtQty.Text)

            Dim con As New SqlConnection(connStr)
            con.Open()

            Dim orderId As Integer = 0

            Dim checkOrderQuery As String = "SELECT TOP 1 Order_Id FROM ORDER_t
WHERE Customer_Id = 1 AND Order_Date = CAST(GETDATE() AS DATE)"
            Dim cmdCheckOrder As New SqlCommand(checkOrderQuery, con)

            Dim result = cmdCheckOrder.ExecuteScalar()

            If result Is Nothing Then
```

```vbnet
        Dim newIdQuery As String = "SELECT ISNULL(MAX(Order_Id),1000)+1
FROM ORDER_t"
        Dim cmdNewId As New SqlCommand(newIdQuery, con)
        orderId = Convert.ToInt32(cmdNewId.ExecuteScalar())

        Dim insertOrderQuery As String = "INSERT INTO ORDER_t VALUES (" &
orderId & ",1,CAST(GETDATE() AS DATE))"
        Dim cmdInsertOrder As New SqlCommand(insertOrderQuery, con)
        cmdInsertOrder.ExecuteNonQuery()

    Else
        orderId = Convert.ToInt32(result)
    End If



        Dim checkLineQuery As String = "SELECT Ordered_Quantity FROM
Order_line_t WHERE Order_Id = " & orderId &
                        " AND Product_Id = " & productId

    Dim cmdCheckLine As New SqlCommand(checkLineQuery, con)
    Dim existingQty = cmdCheckLine.ExecuteScalar()

    If existingQty IsNot Nothing Then

        Dim newQty As Integer = Convert.ToInt32(existingQty) + quantity

        Dim updateQuery As String = "UPDATE Order_line_t SET Ordered_Quantity
= " & newQty &
                        " WHERE Order_Id = " & orderId &
                        " AND Product_Id = " & productId

        Dim cmdUpdate As New SqlCommand(updateQuery, con)
        cmdUpdate.ExecuteNonQuery()

    Else

        Dim insertLineQuery As String = "INSERT INTO Order_line_t VALUES (" &
orderId & "," & productId & "," & quantity & ")"
        Dim cmdInsertLine As New SqlCommand(insertLineQuery, con)
        cmdInsertLine.ExecuteNonQuery()
```

```
        End If

        con.Close()

        lblMessage.Text = "Product added successfully!"

    End If

  End Sub

End Class
```

Cart.aspx:

```
<%@ Page Language="VB" AutoEventWireup="false" CodeFile="Cart.aspx.vb"
Inherits="Cart" %>

<!DOCTYPE html>
<html>
<head runat="server">
   <title>Shopping Cart</title>
   <link rel="stylesheet" href="style.css" />
</head>
<body>

<form id="form1" runat="server">

<header>
   <h1>Shopping Cart</h1>
</header>

<nav>
   <ul>
     <li><a href="main.aspx">Home</a></li>
     <li><a href="search.aspx">Shop</a></li>
   </ul>
</nav>
```

```
<div class="container">

    <div class="product-grid">

        <asp:Repeater ID="rptCart" runat="server">
            <ItemTemplate>
                <div class="product-card">

                    <div class="image-box"></div>

                    <h3><%# Eval("Product_Description") %></h3>

                    <p>Finish: <%# Eval("Product_Finish") %></p>

                    <p>Price: $<%# Eval("Standard_Price") %></p>

                    <p>Quantity: <%# Eval("Ordered_Quantity") %></p>

                </div>
            </ItemTemplate>
        </asp:Repeater>

    </div>

    <br />

    <asp:Label ID="lblMessage" runat="server"
        style="display:block; color:green; margin-bottom:10px;"></asp:Label>

    <asp:Button ID="paymentbtn" runat="server"
    Text="Proceed to   Pay+"
    CssClass="btn"
    PostBackUrl="payment.aspx" />

    <asp:Button ID="btnBack" runat="server"
        Text="Continue Shopping"
        CssClass="btn"
        PostBackUrl="search.aspx" />
```

```
</div>

</form>
</body>
</html>
```

Cart.aspx.vb:

```vbnet
Imports System.Data.SqlClient
Imports System.Configuration

Partial Class Cart
    Inherits System.Web.UI.Page

    Dim connStr As String =
ConfigurationManager.ConnectionStrings("PVFCConnectionString").ConnectionString

    Protected Sub Page_Load(sender As Object, e As EventArgs) Handles Me.Load

        If Not IsPostBack Then
            BindCart()
        End If

    End Sub


    Private Sub BindCart()

        Dim con As New SqlConnection(connStr)

        Dim query As String = "SELECT o.Order_Id, " &
                "p.Product_Description, " &
                "p.Product_Finish, " &
                "p.Standard_Price, " &
                "ol.Ordered_Quantity " &
                "FROM ORDER_t o " &
                "INNER JOIN Order_line_t ol ON o.Order_Id = ol.Order_Id " &
                "INNER JOIN PRODUCT_t p ON ol.Product_Id = p.Product_Id " &
                "WHERE o.Customer_Id = 1 " &
                "ORDER BY o.Order_Id"
```

```vb
        Dim cmd As New SqlCommand(query, con)

        con.Open()

        Dim dr As SqlDataReader = cmd.ExecuteReader()

        rptCart.DataSource = dr
        rptCart.DataBind()

        con.Close()

    End Sub


End Class
```

Payment.aspx:

```aspx
<%@ Page Language="VB" AutoEventWireup="true" CodeFile="payment.aspx.vb"
Inherits="_payment" %>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Payment</title>
    <link rel="stylesheet" href="style.css" />
</head>
<body>
<form id="form1" runat="server">

<header>
    <h1>Payment Options</h1>
</header>

<div class="container">
    <asp:RadioButton ID="rbCash" runat="server" GroupName="Payment" Text="Cash on
Delivery" /><br />
    <asp:RadioButton ID="rbCard" runat="server" GroupName="Payment" Text="Credit/Debit
Card" /><br />
    <asp:RadioButton ID="rbWallet" runat="server" GroupName="Payment" Text="Other Wallet"
```

```
/><br /><br />

    <asp:Button ID="btnConfirm" runat="server" Text="Confirm Payment" CssClass="btn"
OnClick="btnConfirm_Click" /><br /><br />

    <asp:Label ID="lblMessage" runat="server" ForeColor="Green"></asp:Label><br /><br />

    <asp:HyperLink ID="hlBack" runat="server" NavigateUrl="index.aspx">Back</asp:HyperLink>
</div>

</form>
</body>
</html>
```

Payment.aspx.vb:

```
Partial Class _payment
    Inherits System.Web.UI.Page

    Protected Sub btnConfirm_Click(sender As Object, e As EventArgs)
        ' Check which payment method is selected
        If rbCash.Checked Then
            lblMessage.Text = "Cash on Delivery Selected"
        ElseIf rbCard.Checked Then
            lblMessage.Text = "Credit/Debit Card Selected"
        ElseIf rbWallet.Checked Then
            lblMessage.Text = "Wallet Selected"
        Else
            lblMessage.ForeColor = Drawing.Color.Red
            lblMessage.Text = "Please select a payment method"
        End If
    End Sub
End Class
```

Help.aspx:

```
<%@ Page Language="VB" AutoEventWireup="false" CodeFile="Help.aspx.vb" Inherits="Help"
%>

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Help</title>
    <link rel="stylesheet" href="style.css" />
</head>
```

```html
<body>

<form id="form1" runat="server">

<header>
   <h1>Help & User Guide</h1>
</header>

<nav>
   <ul>
      <li><a href="index.aspx">Home</a></li>
      <li><a href="Register.aspx">Register</a></li>
      <li><a href="Search.aspx">Search</a></li>
   </ul>
</nav>

<div class="container">

<h3>New Customer Registration</h3>
<p>Customers can register by filling their name, address, city, state and postal code.</p>
<p><a href="Register.aspx">Go to Registration Page</a></p>

<hr />

<h3>Search Products</h3>
<p>Users can search products by description and product line.</p>
<p><a href="Search.aspx">Go to Search Page</a></p>

<hr />
<h3>Product Catalog Update</h3>
<p>Only employees can update product description, finish and price.</p>
<p><a href="EmployeeLogin.aspx">Employee Login</a></p>

<hr />

<h3>Payment Provision</h3>
<p>Customers can select payment method after placing order.</p>
<p><a href="payment.aspx">Go to Payment Page</a></p>

</div>

<footer>
   Contact us: 0309-5878126 | Email: hhm@gmail.com
```

```
</footer>

</form>

</body>
</html>
```

Help.aspx.vb:

```vb
Partial Class Help
    Inherits System.Web.UI.Page

End Class
```